



CHISSEL PLOUGH

- Specially alloyed steel casting legs unique designed to get the most convenient penetration angle for maximum efficiency.
- Opportunity to work different widths with adjustable legs.
- Reversible shares made of special steel and processed with heat treatment.
- Strong main frame from 100x100mm for CP and 120x120mm for CPA model.
- Bolt secured legs.










OPTIONAL PARTS

- Roller



Roller

TECHNICAL SPECIFICATIONS

MODEL	 Number of Tines (PIECES)	 Clearance (CM)	 Distance between beams (CM)	 Working width (CM)	 Working depth (CM)	 Weigth (KG)	 Power requirement (HP)
CP 005	5	62	30	150	45	328	50-60
CP 007	7	62	30	210	45	418	60-80
CP 009	9	62	30	270	45	516	80-90
CP 011	11	62	30	330	45	689	90-100
CP 013	13	62	30	390	45	790	100-110
CP 015	15	62	30	450	45	900	120-140
CPA 05	5	74	30	150	60	550	70-80
CPA 07	7	74	30	210	60	725	80-90
CPA 09	9	74	30	270	60	880	90-110
CPA 11	11	74	30	330	60	1060	110-130
CPA 13	13	74	30	390	60	1240	130-150
CPA 15	15	74	30	450	60	1450	150-170

ALMEKS

ALMEKS DIŐ TİCARET LTD. ŐTİ.

Kıbrıs Őhitleri Caddesi No: 98 Kat: 6 Daire: 11, 35220 Alsancak - İzmİr / TÜRKiYE

+90(232) 463 7044

+90(232) 463 9433

almeks.com.tr

info@almeks.com.tr

/almeks

YouTube /almeks

Download on the App Store

GET IT ON Google play