



CONVENTIONAL PLOUGH WITH BAR POINT

- Economical solution for stony, rooted, and aggressive soil conditions.
- Cost reduction with use of high resistant bar point comparing to plain share.
- By pushing the bar point forward, getting “first day use plowing quality”.



OPTIONAL PARTS



















- Trash boards
- Deflector
- U-Shape Lower Connection Bar
- Mouldboard Extension
- Slatted Body
- Metal Depth Wheel
- Wing Coulters
- Disc Coulters



U-Shape Lower Connection Bar



TECHNICAL SPECIFICATIONS

MODEL																
	Clearance (CM)	Distance between beams (CM)	Working width (CM)	Working depth (CM)	Weigh (KG)						Power requirement (HP)					
																
KP08	64	59	23,5	20	130	183	266	385	451	517	25-30	35-40	40-45	60-65	70-80	80-90
KP09	65	63	24,5	22	158	229	338	493	628	763	30-35	40-45	45-50	60-70	70-80	85-95
KP10	65	70	25,5	24	172	242	350	511	667	823	30-35	40-45	50-60	70-80	85-90	90-100
KP11	65	71	27,5	24	173	242	353	521	670	830	35-40	45-50	60-70	70-85	90-100	95-105
KP12	65	76	30	26	173	249	373	562	675	837	40-50	45-50	60-70	70-85	90-100	100-120
KP13	65	77	32,5	28	174	251	378	565	688	848	40-50	45-50	70-80	80-85	90-100	110-130
KP14	65	79	35	28	185	251	378	570	690	855	45-50	50-60	70-80	85-95	100-110	120-140
KP16	70	82	37,5	30	205	291	448	630	845	910	50-60	60-70	80-90	90-100	110-120	140-160

ALMEKS

ALMEKS DIŐ TİCARET LTD. ŐTİ.

Kıbrıs Őehitleri Caddesi No: 98 Kat: 6 Daire: 11, 35220 Alsancak - İzmır / TÜRKiYE

+90(232) 463 7044

+90(232) 463 9433

almeks.com.tr

info@almeks.com.tr

/almeks

YouTube /almeks

Download on the App Store

GET IT ON Google play