

CONVENTIONAL PLOUGH WITH BOLT SAFETY

- PP ploughs are equipped with bolt safety system preventing any damage on the tractor and on the plough caused by overloading.
- Easy and quick replacement of the cracked bolt to allow work to continue.
- High resistible frame construction.
- Cheapest solution for fields with few obstacles.



TECHNICAL SPECIFICATIONS

MODEL	Clearance (cm)	Distance between beams (cm)	Working width (cm)	Working depth (cm)	Weight (kg)					Power requirement (hp)				
					2	3	4	5	6	2	3	4	5	6
PP08	60	58	23,5	20	160	249	367	470	573	20-25	30-40	40-50	50-60	60-70
PP09	60	59	24,5	22	162	251	371	490	609	30-40	45-50	50-60	60-70	70-80
PP10	64	67	25,5	24	205	320	488	610	732	30-40	45-50	70-80	80-90	85-95
PP11	64	67	27,5	24	210	330	496	625	754	30-40	50-55	70-85	85-95	95-105
PP12	64	72	30	26	212	340	515	645	775	40-50	55-60	70-85	90-100	100-110
PP13	64	72	32,5	28	214	350	522	655	788	40-50	55-60	70-85	90-100	110-120
PP14	64	73	35	28	215	350	522	655	799	40-50	60-70	80-90	90-110	120-130
PP16	64	73	37,5	30	255	400	541	700	859	50-60	70-80	80-90	100-110	130-140

ALMEKS

ALMEKS DIŐ TİCARET LTD. ŐTİ.

Kıbrıs Őhitleri Caddesi No: 98 Kat: 6 Daire: 11, 35220 Alsancak - İzmır / TÜRKİYE

+90(232) 463 7044

+90(232) 463 9433

almeks.com.tr

info@almeks.com.tr

/almeks

YouTube /almeks

Download on the App Store

Google play