



DISC PLOUGH




- 20-30 % fuel economy in comparison with mouldboard ploughs.
- Standard 660 mm or 710 mm optional discs made from Boron Steel with special concavity.
- Adjustable disc position angle (vertical 3 positions, lateral 5 positions) for use in tough or soft soil conditions.
- 5 level disc penetration angle and 3 level disc position adjustment.
- Excellent solution for rooty, sticky or abrasive soil.
- Flanged frame to add an extension, if required.
- Adjustable and replaceable scrapers not only for cleaning also for overturning.
- Heavy duty rear furrow wheel from hardened steel, spring loaded, full adjustable vertically and laterally, with additional cast weightenings.
- Steel Bearing housings to assure trouble free long operation life.
- Adjustment arm for best tractor- plough alignment.



Adjustment arm










Disc penetration adjustment



Disc position adjustment

TECHNICAL SPECIFICATIONS

MODEL	 Number of Discs (PIECES)	 Disc Diameter (mm)	 Clearance (cm)	 Working width (cm)	 Working depth (cm)	 Weight (kg)	 Power requirement (hp)
DIP02	2	660	68	50-60-70	26	360	40-50
DIP03	3	660	68	70-85-100	26	480	50-60
DIP04	4	660	68	90-110-130	26	580	60-80
DIP05	5	660	68	110-135-160	26	680	80-90
DIP06	6	660	68	130-160-190	26	770	90-110
DIPB03	3	660	68	75	26	423	50-60
DIPB04	4	660	68	100	26	555	60-80

ALMEKS

ALMEKS DIŐ TİCARET LTD. ŐTİ.

Kıbrıs Őehitleri Caddesi No: 98 Kat: 6 Daire: 11, 35220 Alsancak - İZMİR / TÜRKİYE

+90(232) 463 7044

+90(232) 463 9433

almeks.com.tr

info@almeks.com.tr

f /almeks

YouTube /almeks

Download on the App Store

GET IT ON Google play