

ROTARY TILLER

- It is a multi-directional machine, which may easily be used in many procedures such as cultivating soil, seed bed preparation, stubble-ploughing etc. in your field by its strong structure.
- It prevents foot stone formation by setting off the soil by means of its special ripper feet; thus it provides formation of the most appropriate texture for plant root development and plant nutrition.
- It prevents removal of mellowness of soil as it vaporizes by applying pressure onto the soil cultivated by means of optional light and heavy mangle.
- It is an environmentally friendly machine by providing humus increase by organic fertilizer through mixing post-harvest plant residues into the soil.
- It takes movements from power take-off by variable-speed transmission (540, 750 or 1000 cycle/ min.). It allows changing rotation speed of blades in many different options with replaceable gears within the gearbox and it provides efficient fragmentation and mixing procedure.
- It saves on time and fuel oil.



MODEL	Working width (MM)	Working depth (CM)	Overall width (MM)	Overall height (MM)	Number of flanges (PIECE)	Number of Horizontal Blades	Number of Vertical Blades	P.T.O. Shaft Rotations (Max.)(Min-1)	Weigth (KG)	Power requirement (HP)
A-TSR 1200	1260	220	1516	1100	6	30	36	540	390	30-35
A-TSR 1500	1514	220	1770	1100	7	36	44	540	420	35-40
A-TSR 1800	1768	220	2024	1100	8	42	52	540	455	40-45
A-TSR 2000	2022	220	2278	1100	9	48	60	540	490	45-50
TA-TSR 2300	2240	220	2570	1100	10	54	68	540	760	55-65
TA-TSR 2500	2495	220	2825	1230	11	60	76	540	850	70-75
A-TDSR 1500	1514	220	1790	1200	7	36	44	540	575	50-55
A-TDSR 1800	1768	220	2044	1200	8	42	52	540	600	55-60
A-TDSR 2000	2022	220	2298	1200	9	48	60	540	665	60-65
A-TDSR 2300	2240	220	2590	1230	10	54	68	540	785	70-75
A-TDSR 2500	2495	220	2825	1230	11	60	76	540	880	75-80



ALMEKS DIŞ TİCARET LTD. ŞTİ.

Kıbrıs Şehitleri Caddesi No: 98/11 Alsancak - İZMİR / TÜRKİYE



+90(232) 463 7044



+90(232) 463 9433



almeks.com.tr



info@almeks.com.tr







