



# SEED DRILL

- Grains like Wheat, barley, oats, rye, etc: Lentils, legumes such as chickpeas: Alfalfa, canola etc.: small type seeds could be sowing.
- Usable at all tractor and soil conditions. Sowing feet optionally with single disc, double disc, and chisel feet.
- It could using as a hanging type and tractor trailed type.
- The seeds is and fertilizer is continuously leaving to desirable depth and in desirable quantity. Isn't obstruct and do not lake.
- Optionally sowing foots automatic and hydraulic (with lift) adjustable type could be produced.
- Disc sheets is made of special steel material and is with double roller bearing.
- Is produced from quality materials.
- Easy to use, adjustment is simple and is long lasing one machine.
- Sowing (discs) distance could be makes could be 14,2 or 12,5 cm.



- According the soil conditions is possible to mounting a different type of tires.
- The shooter rolls of seeds and fertilizer is made of aluminium. Lower craw is spring bargain. is easy to unload the seeds and fertilizer.
- The norm degree arm beds of seeds and fertilizer is with roller. Don't' make a space.
- The seed and fertilizer hopper covers is separate each to other. Because the severally covers is opening separately is providing a easyness while filling. Is prevent to mixing seeds with fertilizer each to other.
- Its painting with owen painting system. Due to color and metal surfaces resistance has been boosted.
- Our grain seed drill is producing under TS5690 standards and is owning a ``CE`` certificate.

## TECHNICAL SPECIFICATIONS

MODEL	Length (MM)	Width (MM)	Heigth (MM)	Working Width (MM)	Hopper Length (MM)	Disc Distance (MM)	Dipping Depth of the Disc (MM)	Fertilizer Hopper Vol. (Dm³)	Seed Hopper Vol. (Dm³)	Wheel Size	Weigth (KG)	Power requirement (HP)
<b>SD-A 12</b>	2530	3270	1470	1704	1870	125 or 142	0-150	218	327	6.00x16	760	Compatible to all tractor types.
<b>SD-A 14</b>	2810	3270	1470	1988	2150	125 or 142	0-150	245	370	6.00x16	850	
<b>SD-A 16</b>	3090	3270	1470	2272	2430	125 or 142	0-150	272	412	6.00x16	910	
<b>SD-A 18</b>	3370	3270	1470	2556	2710	125 or 142	0-150	300	456	7.50x16	1010	
<b>SD-A 20</b>	3660	3270	1470	2840	3000	125 or 142	0-150	327	500	7.50x16	1085	
<b>SD-A 22</b>	3940	3270	1470	3124	3280	125 or 142	0-150	354	542	7.50x16	1140	
<b>SD-A 24</b>	4220	3270	1470	3408	3560	125 or 142	0-150	381	584	7.50x16	1240	
<b>SD-A 26</b>	4510	3270	1470	3692	3850	125 or 142	0-150	408	626	7.50x16	1325	
<b>SD-A 28</b>	4636	3270	1470	3976	4130	125 or 142	0-150	435	668	7.50x16	1400	



ALMEKS IMPORT & EXPORT Co.

Kıbrıs Şehitleri Caddesi No: 98/11 Alsancak - İZMİR / TÜRKİYE

+90(232) 463 7044

+90(232) 463 9433

almeks.com.tr

info@almeks.com.tr



/almeks



/almeks



Download on the App Store



GET IT ON Google play