

- High resistible, heat treated discs notched at front and plain at rear or alternated.
- Transport tyres also ensure optimum working depth control.
- Ease and speed of set-up into the work/transport position.
- Easy gang angling adjustment with locking device standart manual or Hdroulic (Optional).
- Increased inter-disc spacing and disc scrapers preventing trash built up.
- Hydrolic folding to reduce the transport widt for easy and safe transportation.
- Spacers and bearing housings made from steel for trouble free long working life.
- Hydrolic folding to reduce the transport widt for easy and safe transportation for 32 disc and more.





## TECHNICIAL SPECIFICATIONS

MODEL	Number of Discs (PIECES)	Disc Diameter (MM)	Disc spacing (CM)	Working width	Working depth	Weigth (KG)	Power requirement
CDHV 32	32	610	23	368	20	3180	140-150
CDHV 34	34	610	23	391	20	3250	150-160
CDHV 36	36	610	23	414	20	3360	160-170
CDHV 38	38	610	23	437	20	3430	170-180
CDHV 40	40	610	23	460	20	3500	180-200
CDHV 44	44	610	23	506	20	3640	200-220
CDHV 48	48	610	23	552	20	3780	220-240
CDHV 52	52	610	23	598	20	3920	240-260
CDHV 56	56	610	23	644	20	4060	260-280
CDHV 60	60	610	23	690	20	4200	280-300



Kıbrıs Şehitleri Caddesi No: 98 Kat: 6 Daire: 11, 35220 Alsancak - İzmir / TÜRKİYE

+90(232) 463 9433

🗾 almeks.com.tr

App Store

info@almeks.com.tr

/almeks

**(** +90(232) 463 7044

You Tube /almeks



Google play